


SPE-265/WS - Loudspeaker Pair



Pairs of flush-mount speakers, coaxial system, 8 Ω, tweeter with ferrofluid.

- Moisture-proof
- White one-piece plastic design and plastic cone
- Versatile use for car hi-fi, PA, terrace, boat

Technische gegevens:

Impedance (Z)	: 8 $\hat{\Omega}$
Transmission method	: -
Frequency range	: 80-20,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating	: 30 W
Peak music power output	: 60 W
Sensitivity	: 87 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: Ø 133 mm
Mounting depth	: 60 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: Ø 180 mm x 80 mm
Outside diameter	: Ø 180 mm
Width	: Ø 180 mm

Height	: -
Depth	: 80 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 Â°C
Weight	: 0.8 kg
Packing unit	: -
Type of speaker	: 165